



ANODAL® CLEANER NFB POWDER

Anodal Cleaner NFB Powder is a heavy duty, non-silicate, non-foaming, alkaline soak cleaner that exhibits the following performance characteristics:

- Excellent for removing buffing compounds and job soils.
- Especially recommended for bright parts.
- Does not attack parts.
- Leaves no smut.
- Non-foaming therefore air agitation can be used.

PHYSICAL PROPERTIES:

Appearance: Free flowing powder

APPLICATION DETAILS:

Concentration: 4 - 8 oz/gal.
Temperature: 120°F - 160°F.
Time: 1 - 10 minutes
Equipment: Mild Steel

CONTROL METHOD:

1. Place a 10 ml sample in a 250 ml beaker.
2. Add 8 - 10 drops of Methyl Orange indicator.
3. Titrate with 1.0 N Hydrochloric acid (HCl) to a red endpoint.

Calculations: **Anodal Cleaner NFB (oz/gal) = ml HCl x 1.7**

HANDLING PRECAUTIONS:

Anodal Cleaner NFB is slightly alkaline and may be irritating to some personnel. Rubber gloves should be worn when transferring this material to the processing tank.

WASTE DISPOSAL:

Anodal Cleaner NFB contains biodegradable wetting agents. Solutions of NFB may need pH adjustment in order to meet local ordinance standards prior to disposal.

Recommendations, notices or instructions as to handling, use, storage or disposal of this product, including its use alone or in combination with other products, or as to any apparatus or process for its use are based upon information believed to be reliable. No liability is taken with respect to any such recommendations or instructions. Sole and exclusive warranty is that products comply with published chemical and physical specifications as provided on the certificate of analysis. No other warranties, either express or implied are given.