



## SANODYE® BLUE 2LW

**Sanodye Blue 2LW** produces attractive bright blue shades. This dye demonstrates light fastness properties that make it also suitable for exterior items.

### **PROPERTIES:**

Chemical description:	Anthraquinone dye (granular)
Light fastness:	Architectural quality (8+)
Weather fastness:	Outstanding
Heat fastness:	Moderate up to 400° F.

### **RECOMMENDED APPLICATION DETAILS:**

Concentration:	0.5 - 2.0 g/l
pH range:	5.0 - 6.0
Buffering:	Ammonium acetate with acetic acid
Temperature:	140° - 160° F.
Immersion Time:	2 - 20 minutes

For architectural quality finishes, please refer to the processing requirements as described in the Reliant bulletin, the *Sanodal System*.

### **PREFERRED SEALING METHODS:**

Hot:	Anodal ASL or Anodal AS
Medium:	Anodal MS-1 New or Anodal MTS Plus
Cold:	Anodal CS-2, Anodal CS-2N or Anodal CS3

### **PRECAUTIONS:**

Effective rinsing and normal care to eliminate drag-in are required for best results.

### **ENVIRONMENTAL CONSIDERATIONS:**

This is a RoHS compliant product that contains no heavy metals.

Recommendations, notices or instructions as to handling, use, storage or disposal of this product, including its use alone or in combination with other products, or as to any apparatus or process for its use are based upon information believed to be reliable. No liability is taken with respect to any such recommendations or instructions. Sole and exclusive warranty is that products comply with published chemical and physical specifications as provided on the certificate of analysis. No other warranties, either express or implied are given.