



SANODYE® YELLOW D

Sanodye Yellow D produces an excellent neutral yellow color when used alone. It is extremely useful in mixtures because of its compatibility with so many other dyes.

PROPERTIES:

Chemical description:	Azo dye (powder)
Light fastness:	Fair (5)
Heat fastness:	Moderate up to 300° F.

RECOMMENDED APPLICATION DETAILS:

Concentration:	0.5 - 5.0 g/l
pH range:	5.5 - 6.5
Buffering:	Anodal® Dye Buffer Liquid
Temperature:	140 - 160° F.
Immersion time:	2 - 20 minutes

PREFERRED SEALING METHODS:

Hot:	Anodal ASL or Anodal AS
Medium:	Anodal MS-1 New or Anodal MTS Plus
Cold:	Anodal CS-2, Anodal CS-2N or Anodal CS3

PRECAUTIONS:

This dye is highly resistant to drag-in contamination and consequently has a long tank life with no color shift on aging.

ENVIRONMENTAL CONSIDERATIONS:

This is a RoHS compliant product that contains no heavy metals.

Recommendations, notices or instructions as to handling, use, storage or disposal of this product, including its use alone or in combination with other products, or as to any apparatus or process for its use are based upon information believed to be reliable. No liability is taken with respect to any such recommendations or instructions. Sole and exclusive warranty is that products comply with published chemical and physical specifications as provided on the certificate of analysis. No other warranties, either express or implied are given.